



**Hellberg**



## XS STREAM LD

Bluetooth® hearing protection for music streaming. Xstream LD connects via Bluetooth® to your phone for wireless music streaming and phone calls. Your hearing is protected while you enjoy your favourite music in excellent sound quality, and the built-in voice microphone allows you to make phone calls.

Battery life	55 hours
SNR	29
NRR	25
Weight	386g
Approved by European standards	EN 352-1, 4,6,8 HML 32-26-17
Approved by North American standards	ANSI S3.19-1974 CSA Z94.2-02 Class A
Environmental approval	ROHS, REACH, WEEE
Sound playback	Stereo

  
**Hellberg**  
Since 1962

[www.irudek.com](http://www.irudek.com)

# XS STREAM LD



## BLUETOOTH®

Wireless connection to your mobile phone for easy set-up



## PUSH BUTTON CONTROLS

Push buttons Easy to find and operate even when wearing gloves.



## ACTIVE LISTENING

Microphones in each earpiece allow you to communicate with your colleagues and be alert to alarm signals.



## USB CHARGING

Batteries charge quickly with the included USB charging cable



## WATERPROOF according to IPX4

Can be used in heavy rain



## BATTERY SAFETY FUNCTION

Automatically shuts down the unit after a period of inactivity.



## VOICE ASSISTANT SUPPORT

Compatible with SIRI and Google Assistant. Activate the function and control music playback or phone call with your voice.



## DISEÑADO PARA ESCUCHAR MÚSICA

La excelente calidad de sonido se consigue con un diseño de altavoz patentado que permite disfrutar de una escucha de música de categoría de auriculares en protector auditivo.

## Optional accessories

- Replacement electronics for headband
- Electronic Safe Hygiene Kit
- FRESH" sweatband
- Active listening microphones
- Boom microphone
- Boom microphone boom
- 3.5 mm stereo connection cable



Xstream LD Headband; EN 352-1:2002, H-32dB, M-26dB, L-17dB, SNR29dB

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation	14,6	14,0	18,7	26,7	34,4	33,7	35,6	35,1
Std. dev	3,6	4,0	2,9	2,2	2,2	3,1	2,9	4,9
APV	11,0	10,0	15,8	24,5	32,2	30,6	32,7	30,2



Xstream LD Headband; ANSI S3.19-1974; NRR25, CSA Class A

Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation	17,0	20,2	29,9	38,8	38,6	37,9	39,4	39,8	39,5
Std. dev	3,0	2,6	2,4	3,9	2,4	3,3	3,8	3,0	3,2

# SX STREAM LD

Versión Bluetooth	4.1, A2DP 1.2, HSP 1.1, HFP 1.6
Tipo de batería	Li-Ion
Duración batería	55 horas
Tiempo "stand-by"	100 horas
Tiempo de carga	3 horas
Temperatura de trabajo	-20 °C / +55 °C
SNR	29
NRR	25
Peso	386g
Reproducción de sonido	Estéreo

Aprobado para estándares europeos	EN 352-1, 4, 6, 8 HML 32-26-17
Aprobado para estándares norteamericanos	ANSI S3.19-1974 CSA Z94.2-02 Clase A
Aprobación medioambiental	ROHS, REACH, WEEE