

***DATA SHEET***

**irudek**

**KIT TRIP 11**





## TRIP1

The tripods are anchorage devices designed to enable anchor points during work at confined spaces. This type of work requires the use of one anchor point (at least) which enables to work with efficiency and total safety.

Tripods are made of aluminium, which enables to transport them easily.

### CHARACTERISTICS

- Aluminium alloy head: to add robustness and durability to the system
- Embedded pulley: for a more rigid functioning of the winch (Trip 1)
- 2 aluminium anchorage rings: to connect up to two systems (at least one fall arrest system)
- Aluminium legs: a higher lightness
- Adjustable to 9 different heights
- Robust: capacity up to 500kg loads
- Non-slip rubbers: for an optimal stability
- Safety strap: Prevents unintentional leg movement.
- Certified for work at explosive environments ATEX II 2G Ex h II c T6
- Equipped with transport bag

Code	100209600001
Norm	EN795 B ATEX II 2G Ex h II c T6
Weight	12,1 Kg
Access max. Diameter	1,2-1,8m
Height	1,15-2,15m
Max. Load	500 Kg
Anchorage rings	2
Pulleys on head	1
Height positions	7
Lifetime	Unlimited

### Material

Head	Aluminium
Legs	Aluminium
Rings	Aluminium



## KOALA R15

- Fall arresters with retriever function. Its aluminum housing makes it ideal for high performance and offshore situations. The retriever function is activated by changing the position of the handle arm by pulling a pin.

Norm	EN 360 EN 1496 ANSI Z359-1:2007
Length (m)	15
Weight (Kg)	9
Height (mm)	340 (housing)
Length (mm)	200
Width (mm)	135 (117 housing)
Carga (Kg)	136
Static Strength	15 kN
Impact strength	< 6 kN
Stopping distance	1,42 m
Connector opening (mm)	18
Fall witness	Yes
Lifetime	Unlimited

### Material

Cable	Galvanized steel(4mm)
Housing	Aluminium
Connector	Steel